

Maximum permitted weights and dimensions, goods transport Austria

Height	4.00m
Width	
Motor vehicle/trailer	2.55m
Refrigerated vehicle (minimum thickness of walls - 45mm)	2.60m
Length	
Motor vehicle	12.00m
Trailer	12.00m
Articulated vehicle	16.50m
Road train	18.75m
Car transporter	
· empty	18.75m
· loaded	18.75m
Weight per axle	
single axle	10.0t
drive axle	11.5t
tandem axle of a motor vehicle, with a distance between the axles of	
· less than 1.00m	11.5t
· 1.00m to less than 1.30m	16.0t
· 1.30m to less than 1.80m	18.0t
· 1.30m to less than 1.80m, if the drive axle is fitted with twin tyres and pneumatic suspension or equivalent, or if each drive axle is fitted with twin tyres and the maximum weight per axle does not exceed 9.5t	19.0t
tandem axle of a trailer or semi-trailer, with a distance between the axles of	
· less than 1.00m	11.0t
· 1.00m to less than 1.30m	16.0t
· 1.30m to less than 1.80m	18.0t
· 1.80m or more	20.0t
tridem axle of a trailer or semi-trailer, with a distance between two consecutive axles of	
· 1.30m or less	21.0t
· over 1.30m to 1.40m	24.0t
Maximum permitted weight	
Motor vehicle	
· with 2 axles	18.0t
· with >2 axles	25.0t
· with >2 axles, if the drive axle is fitted with twin tyres and pneumatic suspension or equivalent, or if each drive axle is fitted with twin tyres and the maximum weight per axle does not exceed 9.5t	26.0t
· with >3 axles, if the drive axle is fitted with twin tyres and pneumatic suspension or equivalent, or if each drive axle is fitted with twin tyres and the maximum weight per axle does not exceed 9.5t	32.0t
Trailer (not including semi-trailer)	
· with 1 axle	10.0t
· with 2 axles	18.0t
· with >2 axles	24.0t
Articulated vehicle	40.0t
· articulated vehicle in the first or last leg of a piggyback transport	44.0t
· transport of container or swap body, if it is the first or last leg of a combined transport operation	44.0t
Road train	40.0t

Source: AISÖ, March 2011